



1065 Precision Power Resistance Box

Time Electronics
Calibration, Test & Measurement

- 0.1Ω to 120kΩ
- 1% Accuracy
- 10W per resistor dissipation
- In-line readout
- Mechanically and electrically robust
- Fully screened



Introduction

The 1065 Power Decade Resistance Box is designed to meet the standard for educational, industrial and research & design applications.

Housed in a well ventilated metal case its compact construction make it easily transportable, and when in use it takes up a minimum of bench space.

Resistance ranges from 0.1Ω to 120kΩ with a 1% accuracy. Each resistor has a power rating of 10W and the maximum working voltage is 500V.

Switch contact resistance has been kept to a minimum by the use of multi-wafer switches, each with four parallel, silver-plated, self-wiping contacts. The six in-line dials give a clear numerical readout of the selected resistance.

Specifications

Resistance Range:	0.1Ω to 120 kΩ
No. Of Decades:	6
Increment:	0.1Ω steps
Accuracy:	0.1Ω decade, ±5% 1Ω – 120kΩ decades, ±1%
Rating:	Each resistor 10W
Temperature Coefficient:	<100 ppm per °C
Maximum Voltage:	500 V AC/DC
Residual Resistance:	<20mΩ
Dimensions:	390 x 60 x 150 mm
Weight:	2 kg
Optional Extras:	Calibration Certificate UKAS, or traceable to NPL

Ordering Information

Description	Order Code
Power Resistance Box	1065
N.P.L. Traceable Calibration Certificate	9161
UKAS Calibration Certificate	9114

Time Electronics, Botany Industrial Est. Tonbridge, Kent. England. TN9 1RH.
Tel: +44 (0)1732 355993 Fax: +44 (0)1732 770312 E-mail: mail@timeelectronics.co.uk
www.timeelectronics.co.uk